



Measurement & Analytics | Measurement made easy

MB3600-CH40

FT-NIR solids analyzer

Designed for powders, pellets, grains and agrochemicals

Fast and accurate FT-NIR analysis of solids material



The MB3600-CH40 “Solids Analyser” is designed to perform fast and accurate determination of key physico-chemical attributes of raw materials, in-process or finished products in solid form.

It provides fine and specialty chemical companies a fast and non-destructive alternative to compendial QA/QC analytical methods that are usually slow, expensive and complex.

Those companies must be able to check rapidly and regularly chemical specifications of the different product grades to minimize reworks, downgrading and quality giveaways.

The MB3600-CH40 is particularly adapted to agrochemical suppliers who need to facilitate the safe and efficient use of their crop protection formulations while ensuring protection of workers, end-users and environment.

It is also an ideal tool for fertilizer producers who need to characterize their raw materials and develop predictive indicators for transformation dynamics and fertilization value of organic matter.

The analyser can also be fitted with optional accessories to analyse liquids or gel samples.

Fast, simple to use and maintenance-free analytical tool



Solution Benefits

Traditional QA/QC analytical methods typically require some fractionation, titration, drying, weighing or separation steps to be executed by qualified analytical personnel for assay determination. In contrast, the MB3600-CH40 is a fast, simple to use and maintenance-free analytical tool. Its measurement principle is based on near-infrared spectroscopy, a well-established analytical technique for quantitative determination of chemical and physical properties of solid and liquid chemical samples.

The large number of properties that can be determined from a single MB3600-CH40 measurement combined with the speed and simplicity of analysis make it a very attractive alternative for companies confronted with an increasing demand for multiple time-consuming and reagent-intensive analyses. The results are statistically comparable to those found by traditional laboratory techniques. In addition, the instrument can be used by operators without analytical expertise, and its implementation allows reducing organic solvent consumption and waste generation while increasing sample measurement frequency.

A user-friendly analytical solution

To perform a sample assay with the MB3600-CH40, an operator must simply fill the disposable 20ml vial with product, place the vial into the measurement location and click “OK” to start the measurement scan. Less than a minute later, the result for one or several chemical or physical properties are simultaneously displayed and saved, and the instrument is ready for the next sample. Throughout the whole analysis process, some simple on-screen messages and instructions are displayed via the Horizon QA software to allow even an untrained operator to get accurate results.

Multiple chemical properties determined in few seconds



Rapid development of custom analytical methods

Using the MB3600-CH40, multiple physico-chemical properties can be determined simultaneously on a single sample. This makes the analyzer an excellent operation platform for a host of spectroscopy-based methods, replacing tedious and expensive wet chemical procedures.

It is ready to use for the quick development of custom methods on a wide variety of sample types, including granules, powders, pellets or even liquids. The instrument can be used in QA/QC laboratory for qualification of incoming raw materials or final product certification. With a measurement time of a few seconds, it can also be used at-line as a rapid support tool for process monitoring and verification.

A flexible and complete line of accessories



Wide variety of easily interchangeable accessories

The MB3600-CH40 comes by default with a rotating diffuse reflectance accessory with large sample area for analysis of solids, pellets or powders in scintillation vials.

In addition, it is a scalable analyzer that can be fitted with a variety of easily interchangeable accessories that do not require alignment to accommodate all kinds of samples. Among others, the following sampling options are available:

- Universal heatable vial holder (analysis of liquids and waxes in disposable vials with 5 mm, 8 mm and 12 mm outer diameter)
- Hand-held “pen” probe (powders)
- Fiber-optic launcher to interface with flow-through cells (liquids), transmission probes (liquids), transreflectance probes (opaque liquids) or diffuse reflectance probes (powders)
- Fiber-optic coupled disposable temperature controlled vial (liquids)
- Temperature controlled transmission cell (liquids)

Reliable industrial solution



Straightforward implementation

The MB3600-CH40 is equipped with the modern and intuitive Horizon software suite. It includes a user-friendly operator interface Horizon QA for routine sample analysis and reporting. Quantitative methods for multiple products and properties can be developed and customized with the Horizon Quantify chemometrics package. ABB can also supply calibration services to develop custom calibration methods, based on samples and reference assay values supplied by customer.

Reliable industrial solutions

ABB has been a world leader for many years in industrial analytical solutions. Our laboratory analyzers are renowned for their ruggedness and long-term stability. Our engineers have designed the Solids analyzer with dependable components in order to provide uninterrupted analysis capability without requiring adjustments by analytical expert.

The different accessories are easily interchangeable without requiring optics re-alignment. The aluminum casting of the MB3600-CH40 provides the level of protection required for intensive use in an industrial environment. It also features permanently aligned optics and a light source that has an average lifespan of 10 years, which means that the instrument is virtually maintenance-free. For additional serenity, users can rely on the built-in health monitoring checks that run continuously while the instrument is in operation.

Technical specifications

Spectroscopic performance (typical at 25 °C)

- Spectral Range 3,700 to 15,000 cm^{-1}
- Resolution better than 0.7cm^{-1}
- Apodized Resolution Adjustable 1 cm^{-1} to 64 cm^{-1} (2° increments)
- Short-term stability (@ 8000 cm^{-1}): $< 0.09\%$
- Frequency repeatability (@ 7300 cm^{-1}): $< 0.006\text{ cm}^{-1}$
- Frequency accuracy (@ 7300 cm^{-1}): $< 0.06\text{ cm}^{-1}$
- Absorbance reproducibility (measured on spectroscopic grade toluene): $< 0.002\text{ AU}$

Application software (computer not included)

- Horizon MB FTIR: basic instrument operations and validation
- Horizon MB Quantify: chemometrics, calibration development, instrument qualification
- Horizon QA: Intuitive operator interface for routine analysis and QA/QC operations

Optical bench

- Beamsplitter material: ZnSe (non-hygroscopic)
- Patented double pivot high throughput Michelson interferometer, fully jacketed
- Optical path fully purgeable
- Source: quartz halogen with electronic stabilization
- Metrology: solid-state laser
- Detector module with integrated cooling: extended-InGaAs
- Open sample compartment configuration: Arid-Zone, center focus
- Sample compartment dimensions: $20\text{ cm} \times 14\text{ cm}$ plate, 8.7 cm beam height

Sampling accessories

- Default: rotating Powder Samplir (Diffuse reflectance - Solids)
- Option: Universal heatable vial holder (Transmission – Liquids)
- Option: hand-held “pen” probe (Diffuse reflectance - Powders)
- Option: Fiber-optic launcher to interface with flow-through cells (liquids), transmission probes (liquids), transfectance probes (opaque liquids) or diffuse reflectance probes (powders)
- Option: temperature-controlled cell (Transmission – Liquids)

Data communication

- Hardware port: Ethernet, 10/100 Mbps

Instrument enclosure

- Casting: rugged all-metal with integral handles
- Size: 43.5 cm (W) $\times 28.0\text{ cm}$ (D) $\times 37.2\text{ cm}$ (H)
- Weight: 24 kg

Environmental

- Universal power supply: 120-240 VAC, 50/60 Hz
- Power consumption: 65 W
- Operating temperature: 10°C to 35°C
- Operating relative humidity: 5% to 80%, non-condensing
- Regulatory certification and compliance: TUV and CE

Documentation

- User manual
- Quick-start guide

Contact us

ABB Inc.

Process Automation

Measurement & Analytics

3400, Rue Pierre-Ardouin
Quebec (Quebec) G1P 0B2
Canada

Tel.: +1 418 877-2944

1 800 858-3847 (North America)

Fax: +1 418 877-2834

E-Mail: ftir@ca.abb.com

www.abb.com/analytical

Note

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein.

Any reproduction, disclosure to third parties or utilization of its contents in whole or in parts – is forbidden without prior written consent of ABB.

Copyright© 2015 ABB

All rights reserved



Sales



Service